



DATA SHEET
input terminals
AS 25-SLi
 for busbars for Eurovario series
 Article number 09920186



Function

Terminals for busbars to supply switching devices. Series AS terminals allow the supply to MCBs (one-pole+N).


Features

for 1-pole+N MCBs, load capacity up to 80 A, Eurovario system

Technical Data

Technical Data	AS 25-SLi
Series	AS 25-SLi
Accessories design	input terminal
Number of terminal connections	1
Rated voltage (AC)	max. 690 V
screw-type terminal (supply)	
Allowed types of wires	solid conductor, stranded conductors with ferrule, flexible conductors without ferrule, most flexible conductors without ferrule
Cross section solid	1-wire: 6 mm ² ... 25 mm ²
Cross section flexible with ferrule	4 mm ² ... 16 mm ²
Cross section stranded	1-wire: 6 mm ² ... 25 mm ²
Cross section AWG, solid	9 ... 4
Tightening torque	max. 2 Nm
flange (connecting the device)	
General data	
Installation type	screw
Housing material	polyamide 66 (PA 66)
Protection class	IP20
Width	13 mm
Height	14 mm
Depth	4,8 mm
Weight	0.011 kg
Design requirements/Standards	EN 60664-1

Dimensions



Dimensional drawing Group view

Subject to technical changes

